

Information for users

EN

EN 420+A1:2009 EN 388:2016

PPE CATEGORY II



Read the instructions carefully.

Complies with the requirements of the standard 89/686/EEC

Product: Protective gloves knitted, palm and fingers covered with Nitrile.

Design:	„NITA“	Code:	3630 111 710 XX	Size:	7,8,9,10	Manufacturer design	10851010
Material:	50 % Polyethylene HPPE; 21 % Glass Fiber; 21 % Polyester; 8 % Elastan SPANDEX; coating Nitrile						

Purpose: They may serve as a protection of hands against dirt and protection in the working areas where workers have to face minor mechanical hazards (abrasions, soiling...), for example when handling small loads, handling of sharp-edged objects, pre- assembling, cutting of small dry parts and maintenance. Put the gloves on dry, clean hands.

The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the number, the higher the protection factor)				
A (0-4)	Abrasion resistance:	Performance level 3	 A.B.C.D.E.F.	The protection works only against the specified hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified here. As for the gloves with two or more layers it does not necessarily reflect the properties of the outer layer.
B (0-5)	Blade cut resistance (coupe test)	Performance level 3		
C (0-4)	Tear resistance	Performance level 4		
D (0-4)	Puncture resistance	Performance level 2		
E (A-F)	Cut Resistance (TDM)	Performance level C		
F(P/X) or nothing	Impact protection	Performance level X		
EN 420 - protective gloves (general requirements)				
(1-5)	Dexterity	Performance level 5		
„X“ = test not performed or not applicable..				

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use as a protection against different hazards and classes. Do not use the gloves for handling with flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking.

It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines. Due to the dulling of the blade during the cut resistance test (B) the results of the cut tests are only indicative, while the TDM (E) cut resistance test is the result of the reference design. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles. The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. Thus, you will extend their lifespan. The gloves are designed for single or short-term use only. Dry a damp muff further away from sources of heat at the room temperature. Maximal wash bath temperature 30°C. Any dirt should be brushed out using a soft brush. Do not clean chemically, bleach, dry in a tumble dryer, or iron. Worn through, burned through, strongly fouled or stiffened pairs have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 2 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: The product does not contain any substances, which are known for their adverse impact on hygiene and health of users nor there are suspected of it. In spite of that, the materials which come into contact with a user's skin can cause an allergic reaction in sensitive individuals. If skin irritation or allergic reaction contact your doctor immediately.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment:

Notified Body No. 0075, CTC 4 rue Hermann Frenkel 69367 Lyon cedex 07 France.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents to download".

Marking - example:	
„NITA“	Type of gloves
9	Size
	Pictogram and number of the standard that the product complies with
3342C	Results of the tests carried out
	Conformity mark
cat II	Glove category
	Symbol indicating the necessity to read the instructions
„A“	Production identification
10851010	manufacturer design
	Authorised representative identification

EN420
cat II

EN388
3342C

NITA

3630 111 710 09
1A/2017/237
A

If you need more information, please contact:



U Tesly 1825, 735 41 Petřvald, Czech Republic.