EN ISO 21420:2020 EN 388:2016+A1:2018

PPE CATEGORY II

Read the instructions carefully.

Complies with the requirements of the Regulation (EU) 2016/425

į

Product: Protective gloves against mechanical risks.

Design:	"DINGO"; "DINGO A"	Code:	3210 001 000 XX; 3210 002 000 XX	Size:	9, 11, 12	
Material:	Cow split leather, Cotton, lining palm and fingers.					

Purpose: They may serve as a protection of hands against dirt and protection in the working areas in both dry where workers have to face mechanical hazards (construction, logistics, storage, agriculture, etc.). Put the gloves on dry, clean hands.

The gloves were tested in accordance with EN 388 - mechanical hazards (The higher the							
number, the higher the protection factor)							
A (0-4)		Abrasion resistance:	Performance level 2				
B (0-5)		Cut resistance	Performance level 1	- (<u>4</u> -)			
C (0-4)		Tear resistance	Performance level 3				
D (0-4)		Puncture resistance	Performance level 3				
E (A-F)		Cut Resistance (TDM)	Performance level X	A.B.C.D.E.F.			
F (P/X) or nothing		Impact protection	Performance level X				
EN ISO 21420 - protective gloves (general requirements)							
(1-5) Dexterity		terity	Performance level 2				
X'' = test not performed or not applicable. The test method did not seem appropriate because of the							

material and construction of the glove.

The protection works only against the specified hazards. Do not use the gloves as a protection against different hazards and classes. The results apply only for the model classes, not for the protection levels (classes). The protection levels (classes) are determined based on the tests carried out in accordance with the conditions determined in the valid standards specified here. As for the gloves with two or more layers it does not necessarily reflect the properties of the outer layer. The hand sizing system is based on hand circumference and hand length as defined in EN ISO 2140 Annex B.

Please note: The user must check the gloves before and after use to verify that they are in the required condition. Do not use damaged gloves with holes, cracks, tears Do not use as a protection against different hazards and classes. Do not use the gloves for handling with sharp objects, flames or hot or heated objects, toxic chemicals or greasy objects. Not resistant to soaking.

It is not allowed to wear these gloves in cases with risk of entanglement with moving parts of machines.

For dulling during the cut resistance test (B), the coupe test results are only indicative while the TDM cut resistance test (E) is the reference performance result. The gloves comply with the requirements for puncture resistance. However, they are not meant for protection against thin, sharp objects, such as injection needles.

The mentioned facts may help the user for rational use of this type of protective gloves. It is the responsibility of every user to judge, whether the gloves are used in suitable conditions.

Maintenance, lifetime: After use, make sure the gloves are removed from all pollutants. Thus, you will extend their lifespan. The gloves are designed for single or short-term use only. Dry a damp muff further away from sources of heat at the room temperature. Gloves should not be washed. Any dirt should be brushed out using a soft brush. Do not clean chemically, bleach, dry in a tumble dryer, or iron. Worn through, burned through, strongly fouled or stiffened pairs have to be replaced with new ones. We are not responsible for any reduction of the protective function due to incorrect care. Under suitable storage conditions, shelf life is 5 years.

Storing and transport: Storing in a clean, dry and ventilated place at the room temperature, without any contamination by moisture, dirt, mould, or other agents reducing the level of protection. Do not expose it to solar radiation. The supplier doesn't provide warranty for such damage. Carry them preferably in original package.

Accessories: The product is supplied without accessories.

Dangerous admixtures: Materials which come into contact with the user's skin can cause an allergic reaction in sensitive individuals. They may contain trace amounts of chromium in accordance with the exposure limit values. If skin irritation or allergic reaction contact, do not use gloves and seek medical advice.

Disposal: Dispose of used gloves with respect of the soiling level according to the applicable disposal regulations and the regulations of the local authority. Unused gloves can be disposed of with domestic waste.

The Notified Body that performs conformity assessment: Notified Body No. 1023, INSTITUT PRO TESTOVÁNI A CERTIFIKACI, a. s. T. Bati 299, Louky, 763 02 Zlín, Czech Republic.

The Declaration of Conformity can be found here: www.canis.cz; for individual products, in the bar "Documents".

Marking (sample) - description:						
DINGO	Type of gloves	(i)	Notification on the necessity to read the instructions for use			
11	Size	"A"	Production identification			
EN388	Pictograms and numbers of standards which the product complies with	Exs	Manufacturer's identification			
2133X	Design classes	XX/XXXX XX/XXXX	Month and year of production Use by (month/year)			
C€	Mark of conformity	ZA/XXXX/XXX CAT II	Lot – mark/year/order number PPE category			