


WITH THE FASTENING WHEEL CX5 TWIST



1.

Open the wheel of the tightening system so that the laces can be inserted.



2.

Insert the first end of the lace into the winding wheel.



3.

Tie a knot at the end of the lace.



4.

Trim the excess end.



5.

Pull the lace through the eyelets to the opposite side.




6.

Insert the other end of the lace into the winding wheel.



7.

Make sure that the laces do not cross in front of the wheel.



8.

Tie a knot at the other end of the lace and trim it as in step 4.



9.

Replace the wheel with the button.



10.

Snap the bottom part of the wheel into the base on the shoe and secure it.

Tighten by turning the wheel **to the right** (view when you have your shoes on). Loosen by turning **to the left**. Always tighten only until your foot is comfortably secured; do not overtighten.



watch the instruction video

General safety information

This product is intended solely for securing footwear. Do not use it for other purposes, such as securing equipment. This product is not a toy. Keep out of reach of small children – contains small parts, risk of swallowing or inhalation.

Maintenance and service life

- Clean only with a damp cloth, do not immerse in water or use aggressive chemicals.
- If the cable system is worn or broken, stop using it and replace it.

Disposal

- Dispose of discarded products as plastic/metal waste; do not throw them into municipal mixed waste.

This product is suitable for footwear: Universe Stratus S3S, Universe Cloud S3S, Island Nevis 01, Island Lipari S3, Island Saba S1PS, Texline Lopud S1PS and Fibeline Cerana S3S.